

Kinetrol Model 07 Spring Return Single Acting Actuator

Specification

Angle of Travel (adjustable)

80° - 100°

(restricted travel versions available)

Displaced Volume

300 cm³ / 18.3 in³

Materials of Construction

Casing: Pressure die cast aluminium alloy

Vane & Output Shaft: SG iron, zinc plated

Shaft bushes: PTFE coated bronze (lead free)

Seals: Moulded polyurethane

Seal expanders: Stainless spring steel

Clock Type Spring: Carbon spring steel

Finish

Epoxy stove enamel

Weight

4.54 kg / 10.01 lb (excluding coupling)

Operating Temperature

-40°C to +80°C (-40°F to +176°F)

Spring Torques

Metric Units - Nm

Actuator Model	Position of air OR spring return stroke	Pressure (bar)											
		1.7	2.0	2.4	2.8	3.1	3.5	3.8	4.1	4.5	4.8	5.2	5.5
07-120	Start						30.5	33.9	37.3	40.7	43.5	46.9	50.8
	Finish						19.8	23.7	27.1	30.5	34.4	38.4	42.4

English Units - lbf ins

Actuator Model	Position of air OR spring return stroke	Pressure (psi)											
		25	30	35	40	45	50	55	60	65	70	75	80
07-120	Start						270	300	330	360	385	415	450
	Finish						175	210	240	270	305	340	375

Factory assembled actuator/spring return assemblies have the spring pretension set for "balanced" torque output when the actuator is operated by air at 5.5 bar (80 psi). Factory assemblies can be preset for different air pressures below 5.5 bar (80 psi) on request.

Options

- ISO Flange / Female drive spring option
- Low pressure spring option
- Limit switch boxes for open/closed indication - various switches including hazardous area
- Integral solenoid valve
- AP pneumatic positioner - full range of options
- EL electropneumatic positioner - full range of options
- P3 on/off positioner - full range of options including hazardous area
- Clear Cone monitor
- 180° and 120° model
- ISO adaptor
- Spring to centre
- Geared manual override
- High temperature / Low temperature options
- VDI/VDE 3845 Namur accessory mounting option available - contact Kinetrol
- Available in Blueline paint finish



Kinetrol Model 07 Spring Return Single Acting Actuator

Product Code

Air Ports

Mount Holes

074-120 Metric Spring Return Clockwise	G $\frac{1}{4}$	4 x M8 x 16 deep on 50.9 PCD
074-130 Metric Spring Return Counter Clockwise	G $\frac{1}{4}$	4 x M8 x 16 deep on 50.9 PCD
077-120 English Spring Return Clockwise	$\frac{1}{4}$ NPT	4 x $\frac{5}{16}$ -18 UNC x 0.63" deep on 2.00" PCD
077-130 English Spring Return Counter Clockwise	$\frac{1}{4}$ NPT	4 x $\frac{5}{16}$ -18 UNC x 0.63" deep on 2.00" PCD

For female drive part codes contact Kinetrol

Visual red indicator supplied as standard

Dimensions

