

# Kinetrol Model 03 Spring Unit

## Specification

### Spring Torque

Start 10.3 Nm / 91 lbf ins

Finish 8.7 Nm / 77 lbf ins

For actuated torques see single acting spring return actuator torque data sheets

For reduced spring torques contact Kinetrol

### Angle of Travel

0° - 90°

### Materials of Construction

**Casing:** Pressure die cast ZL16 zinc alloy

**Output Shaft:** Steel, zinc plated

**Clock Type Spring:** Carbon spring steel

### Finish

Epoxy stove enamel


### Weight

1.3 kg / 2.88 lb

### Operating Temperature

-40°C to +80°C (-40°F to +176°F)



 ATEX Category 1

## Options

- ISO Flange / Female drive spring option
- High temperature / Low temperature options
- ISO adaptor
- Available in Blueline paint finish
- Low pressure spring option

## Non Kinetrol Actuator Application Notes

Kinetrol spring units can be used in non Kinetrol actuator applications however the following must be considered.

A static gasket is provided to seal the base plate mounting face but the user's shaft must also be sealed to prevent water ingress into the spring housing.

External stops will need to be used to prevent the spring angle of travel from exceeding 90°.

See Kinetrol installation, operation and maintenance instructions for application example.

# Kinetrol Model 03 Spring Unit

## Product Code

034-020

Metric Spring Return Clockwise

034-030

Metric Spring Return Counter Clockwise

037-020

English Spring Return Clockwise

037-030

English Spring Return Counter Clockwise

## ● Mount Holes

4 x M5 x 10 deep on 31.1 PCD

4 x M5 x 10 deep on 31.1 PCD

4 x 10-24 UNC x 0.39" deep on 1.225" PCD

4 x 10-24 UNC x 0.39" deep on 1.225" PCD

For female drive part codes contact Kinetrol

## Dimensions

