

Kinetrol ISO/DIN Actuator Options

- Direct mounting flange and coupling for mounting to valves with ISO 5211 drive interfaces available for actuator models 02 to 21
- Female star drive for models 02, 03, 05, 07, 09, 12 and 14. All other models are female square drive.



Actuator Model	A mm	B mm	C mm	H mm	ØF mm	ISO/DIN flange no.	M* mm	V mm	ØU mm	PCD mm	N No.	W	Y(Min) mm	J mm	E † mm	P Port	G2 mm	S2 mm
023-100	91	76	24.1	66	29	F03	9	46	25	36	4	M5	8	2	10	G $\frac{1}{8}$	8.0	10.0
033-100	113	92	28.0	74	36	F03	9	46	25	36	4	M5	8	2	10	G $\frac{1}{8}$	9.0	12.0
053-100	132	114	33.6	81	66	F04	11	47	30	42	4	M5	8	2	12	G $\frac{1}{8}$	9.5	13.0
073-100	178	147	43.4	117	68	F05	14	64	35	50	4	M6	10	3	16	G $\frac{1}{4}$	16.0	20.0
083-100	208	167	46.3	133	65	F07	17	70	55	70	4	M8	16	3	19	G $\frac{1}{4}$	16.0	20.0
093-100	227	187	54.7	146	84	F07	17	85	55	70	4	M8	13	3	19	G $\frac{1}{4}$	16.0	20.0
103-100	229	188	57.0	175	77	F10	22	-	-	102	4	M10	16	-	24	G $\frac{1}{4}$	16.0	20.0
123-100	294	239	68.0	181	100	F10	22	125	70	102	4	M10	16	3	24	G $\frac{3}{8}$	16.0	35.5
143-100	380	308	84.0	227	128	F12	27	150	85	125	4	M12	20	3	29	G $\frac{1}{2}$	16.0	35.5
153-100	433	353	101.0	290	138	F14	36	133	100	140	4	M16	38	4	45	G $\frac{1}{2}$	16.0	35.5
163-100	530	427	125.0	380	175	F16	46	203	130	165	4	M20	32	4	48	G $\frac{1}{2}$	41.0	55.0
183-100	680	554	162.0	501	286	F25	55	300	200	254	8	M16	24	4	57	G1	57.0	78.0
213-100	842	660	189.0	594	410	F30	75	350	230	298	8	M20	30	4	77	G1	73.0	100.0

† Minimum

* Models 02, 03, 05, 07, 09, 12 and 14 are female star drive, all other models are female square drive

